GREASES

RED RUBBER GREASE.

A bentone-thickened, vegetable-oil-based grease for brake and hydraulic assembly.

PRODUCT RANGE
Automotive Greases

> 260 °C	2 / 3	Red
Dropping point	NLGI grade	Colour

APPLICATION

- Brake caliper and cylinder assembly
- Rubber seals and boots
- Hydraulic system assembly
- Anywhere a mineral grease would swell the seal

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth grease**
Colour	ASTM D1500	**Red**
NLGI Classification		**2 / 3**
Thickener		**Bentone**
Worked Penetration		**250 to 280**
Base Oil		**A blend of vegetable oils**
Dropping Point (ASTM D2265), °C		**> 260**
Effect On Natural Rubber (volume change), %		**+1% to +6**
Effect On Neoprene Rubber (volume change), %		**-10% to + 10**
Steel Weight change mg/cm²		**0.2**
Aluminium alloy Weight change mg/cm²		**0.1**
Copper Weight change mg/cm²		**0.5**
Cast Iron Weight change mg/cm²		**0.0**
High Temperature Stability @ 120°C		**No polymerization**
Operating Temperature Range, °C		**-5°C to +120**

Typical values. They do not form a specification.

PACK SIZES

500 g, 3 kg, 12.5 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0890

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063