TEXTILE LUBRICANTS

# RING OIL 32.

RING OIL 32 is formulated for the lubrication of a wide variety of spinning and twisting rings, including sintered rings.

PRODUCT RANGE
**Machine Lubricants**

| 28.8-35.2 cSt | 0.870 | Below -5 °C |
|---|---|---|
| Viscosity @ 40°C | Specific Gravity @15.6 | Pour point |

## APPLICATION

- Lubrication of ring spinning
- Solid and sintered rings

**NOT RECOMMENDED**

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

## BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance | Visual | **Pale Amber Oil** |
| Specific Gravity @15.6°C | | **0.870** |
| Viscosity @ 40°C, cSt | | **28.8-35.2** |
| Pour Point, °C | ASTM D97 | **Below -5** |
| Cloud Point, °C | | **>70** |
| Moisture, % | | **0.5** |

Typical values. They do not form a specification.

## PACK SIZES

25 L, 205 L, 1000 L IBC

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS RING 32

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063