TEXTILE LUBRICANTS

RING OIL 68.

RING OIL 68 is formulated for the lubrication of a wide variety of spinning and twisting rings, including sintered rings.

PRODUCT RANGE
Machine Lubricants

61.2-74.8 cSt	0.892	Below -5 °C
Viscosity @ 40°C	Specific Gravity @15.6	Pour point

APPLICATION

- Lubrication of ring spinning
- Solid and sintered rings

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale Amber Oil**
Specific Gravity @15.6°C		**0.892**
Viscosity @ 40°C, cSt		**61.2-74.8**
Pour Point, °C	ASTM D97	**Below -5**
Cloud Point, °C		**>70**
Moisture, %		**0.5**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS RING 68

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063