INDUSTRIAL OILS

ROCK DRILL OIL 46.

A light-viscosity rock drill oil for pneumatic percussion equipment, combining strong EP/anti-wear protection with a tackiness additive that keeps an oil film on cylinder walls under constant air-tool operation.

PRODUCT RANGE
Industrial Specialities

46 cSt	>225 °C	-39 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Air-operated rock drills, jackhammers and pile drivers
- Pneumatic tools: air saws, riveters and torque wrenches
- Mining, quarrying, construction and excavation equipment

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Brown liquid**
Density @ 20°C, kg/m³	ISO 22241-2	**0.896**
Kinematic Viscosity @ 40°C, cSt		**46**
Flash Point, °C	ASTM D92	**>225**
Pour Point, °C	ASTM D97	**-39**

Typical values. They do not form a specification.

PACK SIZES

20 L; 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS RD0046

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063