INDUSTRIAL OILS

ROCK DRILL OIL HEAVY EP 320.

An extreme-pressure rock drill oil for air tools operating under the most demanding boundary-lubrication conditions, with a flow improver for use at low temperatures and enhanced demulsification for slideway protection.

PRODUCT RANGE
Industrial Specialities

300 mm²/s cSt	0.893	>200 °C	-15 °C
Viscosity @ 40°C	Density @ 15	Flash point	Pour point

APPLICATION

- Rock drills, road drills, pneumatic pile drivers, jack hammers, air speed saws and torque wrenches
- Air motors and pneumatic rams/cylinders
- Demolition and chipping hammers, drifters, and heavy industrial pneumatic applications

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40°C, mm²/s		**300**
Kinematic Viscosity @ 100°C, mm²/s		**24.0**
Flash Point (COC), °C		**>200**
Density @ 15°C	ASTM D4052	**0.893**
Pour Point, °C	ASTM D97	**-15**
Copper Corrosion, 3hr @ 100°C (ASTM D130)		**Class 1b**
Rust Test, Synthetic Sea Water (ASTM D665)		**Pass**
Four Ball EP Test, Wear Scar, 20kg/60min (IP239), mm		**0.285**
Timken OK Load (IP240)		**60 lb**
FZG Gear Test, pass load		**12**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS RD0300

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063