INDUSTRIAL OILS

ROCK DRILL OIL ULTRA EP.

A synthetic-base range of rock drill oils across three viscosity grades, combining oxidation-resistant base stocks with rust, foam, extreme-pressure and tackiness additives for long, trouble-free service in air-operated

PRODUCT RANGE
Industrial Specialities

APPLICATION

- Pneumatic drills, jumbo drills, jackleg drills and jackhammers
- Small air tools, air motors and airline oilers

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (all grades)		**Brown liquid**
Kinematic Viscosity @ 40°C, ISO 100, cSt		**100**
Kinematic Viscosity @ 40°C, ISO 220, cSt		**220**
Kinematic Viscosity @ 40°C, ISO 320, cSt		**320**
Density @ 20°C, ISO 100 / 220 / 320, kg/m³		**0.889 / 0.896 / 0.899**
Flash Point, ISO 100 / 220 / 320, °C		**>220 / >225 / >230**
Pour Point, ISO 100 / 220, °C		**-39**
Pour Point, ISO 320, °C		**-42**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS RDSSV

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063