AUTOMOTIVE

RUNNING-IN OIL SAE 30.

Short-term running-in oil for new or reconditioned diesel and petrol engines, used for the bedding-in period before the first service fill.

PRODUCT RANGE
Passenger Car Engine Oils

11.5 cSt	0.876	> 220 °C	-30 °C
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Pour point

APPLICATION

- New engine bedding-in
- Reconditioned and rebuilt engines
- Engine builders and rebuilders

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

SAE	30 monograde

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 30**
Base Oil		**Mineral**
Specific Gravity @ 15.6°C		**0.876**
Kinematic Viscosity @ 100°C, cSt		**11.5**
Viscosity Index	ASTM D2270	**101**
Flash Point (COC), °C		**> 220**
Pour Point, °C	ASTM D97	**-30**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0018

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063