INDUSTRIAL OILS

SARCHAIN HT 550G.

A graphited synthetic ester chain lubricant for the hottest chain applications there are.

PRODUCT RANGE
Chain Lubricants

APPLICATION

- Furnace and kiln conveyor chain
- Heat treatment line chain
- Very high temperature drive chain
- Chains running past 300 °C where nothing liquid survives

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Black liquid**
Base Fluid		**Synthetic ester**
Viscosity @ 40°C, cSt		**220 min**
Specific Gravity @ 20°C		**1.01**
Temperature Range		**10 to 225°C as a fluid lubricant or up to 550°C as a dry film lubricant**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IB0550

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063