METALWORKING FLUIDS

SARCLIP 8.

SARCLIP 8 is a protection and penetrating oil based on specially selected low viscosity highly refined mineral oils combined with corrosion inhibiting and moisture displacing additives, for protection and coating of scaf

PRODUCT RANGE
Anti-Corrosion Products

8 cSt	0.798	135 °C	-18 °C
Viscosity @ 40°C	Specific Gravity @ 20	Flash point	Pour point

APPLICATION

- Scaffolding joints and components
- Fittings and screw threads

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity @ 40°C mm2/s		8
Appearance / Colour		Clear Pale Straw
Specific Gravity @ 20°C		0.798
Pour Point °C, °C		-18
Flash Point °C, °C		135
Aromatic Content, %		<8
Indoor Protection		3-6 Months
Outdoor Protection Covered		Not Recommended
Outdoor Protection Uncovered		Not Recommended

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO008

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063