METALWORKING FLUIDS

SARCOAT PW38 EXTRA.

SARCOAT PW38 EXTRA is a high quality, wax film long term rust preventative with a combination of dewatering additive technology together with film-forming corrosion prevention capabilities to provide extensive long-term

PRODUCT RANGE
Anti-Corrosion Products

APPLICATION

- Metal stocks
- Agricultural machinery
- Vehicle panels
- Bar and box sections
- Aerospace applications

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Opaque fluid**
Film thickness		**40-50 microns**
Solids Content, %		**34-36**
Density @ 15.6°C		**0.83**
Salt Spray ASTM B117		**>1000 hours**
Coverage		**7m² per litre at 50 micron**
Drying time		**@ 20°C to 50 µ film thickness, 3 hours**
Indoor Protection		**5 Years**
Outdoor Protection Covered		**3 Years**
Outdoor Protection Uncovered		**2 Years**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0916

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063