METALWORKING FLUIDS

SARCOOL ECO 3600.

SARCOOL ECO 3600 is a biocide-free, high lubricity, semi synthetic, micro-emulsion coolant designed for arduous machining of tough ferrous and non-ferrous alloys, with passivation for non-staining contact with copper all

PRODUCT RANGE

Soluble Cutting Fluids

APPLICATION

- steels
- aluminium
- yellow metals
- sensitive and special coated alloys
- brass and copper alloys

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (Concentrate)		**Amber liquid**
Appearance (Emulsion)		**Milky**
pH (5% emulsion)		**9.1 – 9.3**
IP 287 Breakpoint, %		**2.5**
Mineral Oil Content		**Medium**
Refractometer Conversion Factor		**1.0**
Make Up Water Hardness, ppm		**50 – 400**
Light – Medium Duty, %		**4.0% – 6.0**
Heavy Duty, %		**6.0% – 8.0**
Very Heavy Duty, %		**8.0% – 10.0**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IC0360

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063