METALWORKING FLUIDS

SARCOOL ML-FF.

SARCOOL ML-FF is a unique semi-synthetic, high-performance rolling and forming fluid designed to produce a wide variety of tube and sheet from galvanised, aluminium, mild steel through to stainless steel materials.

PRODUCT RANGE
Drawing & Forming Oils

APPLICATION

- Galvanised tube
- mild steel tube
- aluminium tube
- stainless steel tube
- sheet rolling
- metal forming

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour (Concentrate)		**Amber**
Emulsion (Appearance)		**Micro**
IP287 Corrosion Break Point %, %		**2.5**
pH (Concentrate as Range)		**9.5 – 10.0**
pH (Typical Operating as Range)		**8.8 – 9.5**
Coolant Refractometer Factor		**1.7**
Oil Content, %		**25**
Light duty concentration, %		**5.0% – 6.0**
Moderate duty concentration, %		**6.0% – 8.0**
Heavy duty concentration, %		**8.0% – 10.0**
Design Concentration Range, %		**5.0% – 10.0**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IC0706

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063