METALWORKING FLUIDS

SARCOOL TEC 5628.

SARCOOL TEC 5628 is a medium to high lubrication, semi-synthetic microemulsion coolant offering excellent cooling and mechanical lubricity, designed for cast iron machining and grinding and suitable for mixed metals incl

PRODUCT RANGE
Soluble Cutting Fluids

APPLICATION

- band sawing
- grinding
- drilling
- milling
- reaming
- tapping
- threading

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (Concentrate)		**Amber liquid**
Appearance (Emulsion)		**Semi translucent**
pH (5% emulsion)		**9.0 – 9.5**
IP 287 Breakpoint, %		**2.5**
Mineral Oil Content		**Medium**
Refractometer Conversion Factor		**1.6**
Make Up Water Hardness, ppm		**0 – 450**
Light Duty, %		**5.0% – 6.0**
Medium Duty, %		**7.0% – 8.0**
Heavy Duty, %		**8.0% – 10.0**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IC05628

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063