METALWORKING FLUIDS

SARCOOL ULTRA.

SARCOOL ULTRA is a high oil content, bio-stable, water soluble cutting fluid for applications where maximum EP performance and low foaming are required, with an optimized lubricity and extreme pressure formulation.

PRODUCT RANGE

Soluble Cutting Fluids

APPLICATION

- boring
- centreless grinding
- deep hole drilling
- drilling
- heavy duty machining centre work
- high-speed turning
- milling
- reaming
- sawing
- tapping
- turning
- aerospace
- automotive
- energy industries

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (Concentrate)		**Amber liquid**
Appearance (Emulsion)		**Milky**
pH (5% emulsion)		**9.0 – 9.4**
IP 287 Breakpoint, %		**2.0**
Mineral Oil Content		**High**
Refractometer Conversion Factor		**1.0**
Make Up Water Hardness, ppm		**80 – 400**
Light Duty, %		**5.0–6.0**
Medium Duty, %		**7.0–8.0**
Heavy Duty, %		**8.0–10.0**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IC0682

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063