METALWORKING FLUIDS

SARCUT ASF 10 M.

Low viscosity high performance chlorine free oil developed for difficult to severe machining operations on high tensile materials, stainless steels, forged steels etc., with high levels of inactive sulphur EP and lubrici

PRODUCT RANGE
Neat Cutting Oils

10 – 12 cSt	0.851	Brown
Viscosity @ 40°C	Specific Gravity @ 15.6	Appearance

APPLICATION

- heavy duty broaching
- high speed machining
- deep hole boring
- medium to high tensile steel and stainless steel alloys

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Brown**
Specific Gravity @ 15.6°C		**0.851**
Kinematic Viscosity @ 40°C, cSt		**10 – 12**
Chlorine	ASTM D808	**No**
Sulphur		**Yes – Active**
Ester		**Yes**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0550

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063