METALWORKING FLUIDS

SARCUT CF 10.

A low viscosity neat cutting oil with a high proportion of lubricity additives, suitable for operations where no sulphur is required.

PRODUCT RANGE
Neat Cutting Oils

APPLICATION

- tapping
- broaching
- deep hole drilling
- ferrous and non-ferrous (yellow) metals

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber Oil**
Specific Gravity @ 15.6°C		**0.950 – 1.05**
Kinematic Viscosity @ 40°C, cSt		**9.00 – 11.4**
Chlorine	ASTM D808	**Yes**
Sulphur		**No**
Ester		**Yes**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0182

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063