METALWORKING FLUIDS

SARCUT CUTTING & TAPPING PASTE.

Based on a highly effective combination of extreme pressure and lubricity additives to promote ease of cutting and prolong tool life.

PRODUCT RANGE
Tapping & Reaming Oils

APPLICATION

- Drilling
- Sawing
- Thread cutting
- High alloy steels and nonferrous metals
- Brush application or dipping small cutting tools

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

PACK SIZES

3 Kg Tins (5 x 3 Kg per case)

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0419

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063