METALWORKING FLUIDS

# SARCUT EXTRA HONING OIL.

A blend of high quality solvent-refined mineral oil and a carefully balanced additive system.

PRODUCT RANGE
**Honing Oils**

## APPLICATION

- Honing operations
- grinding
- drilling
- general machining for ferrous and non-ferrous materials
- cylinders
- gears
- control bushes
- injection pumps

### NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

## BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Colour & Appearance | | **Amber fluid** |
| Density @ 15.6°C, kg/m³ | | **0.890–0.900** |
| Kinematic Viscosity @ 40°C, cSt | | **17–18** |
| Chlorine | ASTM D808 | **No** |
| Sulphur | | **Yes** |
| Ester | | **Yes** |

Typical values. They do not form a specification.

## PACK SIZES

25 L, 205 L, 1000 L IBC

### HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0004

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063