METALWORKING FLUIDS

# SARCUT NEAT 25 CF.

A low viscosity, high performance neat cutting oil free of chlorine and sulphur but with a high proportion of lubricity additives, suitable for operations where no sulphur is required.

PRODUCT RANGE
**Neat Cutting Oils**

## APPLICATION

- medium to heavy duty general machining
- tapping
- broaching
- deep hole drilling operations

### NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

## BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance | Visual | **Amber Oil** |
| Specific Gravity @ 15.6°C | | **0.857** |
| Kinematic Viscosity @ 40°C, cSt | | **24.0 – 26.0** |
| Copper Corrosion ASTM D130 | | **1a** |
| Chlorine | ASTM D808 | **No** |
| Sulphur | | **No** |
| Ester | | **Yes** |

Typical values. They do not form a specification.

## PACK SIZES

25 L, 205 L, 1000 L IBC

### HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0170

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063