METALWORKING FLUIDS

SARCUT ULTRA HONING OIL.

A blend of high quality solvent-refined mineral oil and a carefully balanced EP additive system, formulated with inactive sulphur and a copper passivator for yellow metal protection.

PRODUCT RANGE
Honing Oils

APPLICATION

- Heavy duty honing of ferrous and non-ferrous materials
- Grinding
- Drilling
- General machining operations
- Industrial cylinders and tubes

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Amber fluid**
Density @ 15.6°C, kg/m³		**0.890-0.900**
Kinematic Viscosity @ 40°C, cSt		**18-20**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0007

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063