METALWORKING FLUIDS

SARCUT XP 15.

A technically advanced neat cutting and grinding fluid formulated using an advanced vegetable ester for enhanced polar lubrication, with extreme pressure additives for arduous metal cutting and grinding applications.

PRODUCT RANGE
Neat Cutting Oils

10.0 cSt	**0.854**	**> 200** °C
Viscosity @ 40°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- machining and grinding medium to high tensile steel
- yellow metals
- aluminium alloys and stainless steel
- high speed sliding head and multi-slide machines

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Light amber**
Specific Gravity @ 15.6°C		**0.854**
Kinematic Viscosity @ 40°C, cSt		**10.0**
Copper Corrosion Test		**1a**
Flashpoint, °C		**> 200**
Sulphur		**Yes**
Chlorine	ASTM D808	**No**
Ester		**Yes**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0954

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063