METALWORKING FLUIDS

SARDRAW 196.

SARDRAW 196 is a high-performance heavy duty drawing lubricant for use on ferrous and non-ferrous materials, combining selected additive technology and base oil structure for extreme pressure performance under arduous de

PRODUCT RANGE
Drawing & Forming Oils

APPLICATION

- Heavy duty to severe applications such as heavy duty drawing and stamping of ferrous and non-ferrous materials

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40°C, cSt		**44.0**
Appearance	Visual	**Pale Amber liquid**
Flashpoint, °C		**> 180**
Chlorine	ASTM D808	**Yes**
Sulphur		**No**
Lubricity		**Yes**
Copper Corrosion	ASTM D130	**1b**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0934

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063