METALWORKING FLUIDS

SARDRAW 213.

SARDRAW 213 is a blend of severely solvent-refined oil, EP additives, lubricity esters, corrosion inhibitors, and phosphorous and sulphurised compounds, giving high film strength suitable for a wide range of presswork ap

PRODUCT RANGE
Drawing & Forming Oils

44.0 cSt	> 180C °C	Yes
Viscosity @ 40°C	Flash point	pH

APPLICATION

- Cold forging
- Heavy duty stamping
- Cold reduction/drawing of ferrous materials
- Blanking
- Fine blanking
- Drawing of bar and tube
- Cold heading

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40C, cSt		**44.0**
Appearance	Visual	**Pale Brown liquid**
Flashpoint		**> 180C**
Sulphur		**Yes**
Chlorine	ASTM D808	**Yes**
Phosphorous		**Yes**
Ester		**Yes**
Copper Corrosion	ASTM D130	**1B**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0931

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063