FOOD GRADE

SARFOOD 3H GREASE.

The only product in the range carrying NSF 3H, and that category is the significant thing: 3H permits direct contact with food, not merely incidental contact.

PRODUCT RANGE

Food Grade Release & Assembly Compounds

APPLICATION

- Release agent on grills, ovens and loaf pans
- Chopping boards and butchery benches
- Direct food contact surfaces
- Bearings and slides in the same production area

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

PERFORMANCE PROFILE

Suitable where the following specifications are required:

NSF	3H, H1
USDA	1998 H1 Guidelines
FDA	listed ingredients
No	genetically-modified ingredients
Contains	no nut oil or derivatives

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White grease**
NLGI Classification		**No.1**
Thickener		**Inorganic thickener**
Drop Point (IP 132)		**None**
Base Oil		**Blend of white oils**
Solid Lubricant		**Direct food additives**
Copper Corrosion (IP 112)		**Pass**
Water washout (ASTM DS1264) @ 38°C		**< 2% max.**
Dynamic Corrosion Resistance (EMCOR) (IP 220)		**0:0**
Four Ball (IP 239) Weld Load		**400 kg**
Operating Temperature Range, °C		**-30°C to + 120**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0918

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063