FOOD GRADE

SARFOOD ANTIFREEZE.

A non-toxic food grade antifreeze on mono propylene glycol rather than the ethylene glycol used in every automotive coolant.

PRODUCT RANGE
Food Grade Specialities

35 cSt	1.03	230 °C	-50 °C
Viscosity @ 40°C	Specific gravity @15	Flash point	Pour point

APPLICATION

- Secondary refrigeration on chillers and cold stores
- Blast freezer glycol circuits
- Brewery and dairy cooling systems
- Any coolant circuit near open product

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Meets	the requirements of InS G6 Guidelines

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale-coloured liquid**
Specific gravity @15°C		**1.03**
Kinematic Viscosity @40°C (ASTM D445), cSt		**35**
Viscosity Index (ASTM D2270)		**281**
Flash Point °C (COC)		**230**
Pour Point, °C		**-50**
Specific Heat Capacity kJ/kg Kelvin		**1.95**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0948

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063