FOOD GRADE

SARFOOD ASSEMBLY GREASE.

A high-solids food grade assembly paste, and the food plant answer to copper anti-seize, which cannot be used anywhere near product.

PRODUCT RANGE

Food Grade Release & Assembly Compounds

APPLICATION

- Anti-seize on threaded fasteners in food areas
- Assembly and running-in of bushes and bearings
- Small open plastic or metal gears
- Where a ceramic paste is specified

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Off white smooth paste**
Carrier		**Synthetic Oil**
Base Oil Viscosity @ 40°C, cSt		**320**
Solid lubricant		**White lubricating solids**
EMCOR (IP 220)		**0:0**
Coefficient of friction		**0.12**
Water washout (ASTM D1264) @ 38°C		**< 1% max.**
Four Ball Weld Load (IP 239)		**600kg**
Operating Temperature Range (service lubricant), °C		**-30°C to +150**
Operating Temperature Range (anti-seize lubricant), °C		**-30°C to +100**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 5 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FDA	listed ingredients
NSF	and InS H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients
Contains	no nut oil or derivatives

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0099

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063