FOOD GRADE

SARFOOD HEAT TRANSFER OIL 32.

A food grade thermal fluid for closed circuit and pressureless heat transfer systems, and the one product in this range approved for both direct food contact (Class HT1) and incidental contact (H1).

PRODUCT RANGE
Food Grade Heat Transfer Oils

32 cSt	0.869	218 °C	-18 °C
Viscosity @ 40°C	Density @ 15°C g/mL	Flash point	Pour point

APPLICATION

- Jacketed cooking and process vessels
- Fryers and direct heat process systems
- Closed circuit thermal fluid heating
- Applications requiring an HT1 classified fluid

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear and Bright**
Density @ 15°C g/mL		**0.869**
Viscosity @ 40°C, cSt		**32**
Flash Point, °C		**218**
Fire Point, °C		**256**
Pour Point, °C		**-18**
Max. Oil Film Temperature, °C		**340**
Max. Bulk Oil Temperature, °C		**325**
Coefficient of Thermal Expansion % /, °C		**0.0915**
Coefficient of Thermal Expansion per, °C		**0.000760**

Typical values. They do not form a specification.

PACK SIZES

5 L | 20 L | 205 L

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	components are FDA compliant
Contains	no genetically-modified ingredients, no nut oil or derivative
Kosher	certified
Pareve	certified
Halal	certified
Manufactured	to FLT Quality Standards and Good Manufacturing Practice

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SFHT0032

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063