FOOD GRADE

SARFOOD HIGH TEMP 2 GREASE.

A silica-thickened silicone grease with PTFE, working from -20 °C to +220 °C and formulated to resist the chemical cleaning solutions used in food and drink production.

PRODUCT RANGE
Food Grade Greases

APPLICATION

- Bearings exposed to CIP cleaning chemicals
- High temperature food plant bearings
- Drinking water applications (WRAS)
- Sliding surfaces in aggressive wash environments

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

FOOD GRADE · CONTINUED

SARFOOD HIGH TEMP 2 GREASE.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	ingredients are FDA listed
NSF	and InS H1 Guidelines
USDA	1998 H1 Guidelines
Water	Regulations Advisory Scheme (WRAS) approval
No	genetically-modified ingredients, nut oil or derivatives

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White semi-translucent grease**
NLGI Classification		**No. 2**
Thickener		**Silica**
Base Oil		**High viscosity silicone oil**
Solid Lubricant		**PTFE**
Copper Corrosion (IP 112)		**Pass**
Drop Point (IP 132)		**None**
Water Washout (ASTM D1264) @ 38°C		**< 2% max.**
Dynamic Corrosion Resistance (EMCOR) (IP220)		**0:0**
Shell Four Ball (IP239) Weld Load		**180 kg**
Shell Four Ball (IP239) Mean Hertz Load		**30 kg**
Operating Temperature Range, °C		**-20°C to +220**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0098

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063