FOOD GRADE

# SARFOOD HTS 2 GREASE.

A PAO and polymer grease on a modified inorganic bentone thickener, with a drop point above 280 °C.

PRODUCT RANGE
**Food Grade Greases**

## APPLICATION

- Hot bearings on long relubrication intervals
- Oven and dryer bearing points
- High water resistance requirements
- Where a soap grease would melt out

**NOT RECOMMENDED**

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **All** | ingredients are FDA listed |
| **Meets** | NSF and InS H1 Guidelines, USDA 1998 H1 Guidelines |
| **Contains** | no genetically-modified ingredients, nut oil, or derivatives |

## BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance | Visual | **Off white smooth grease** |
| NLGI Classification | | **No.2** |
| Thickener | | **Bentone** |
| Drop Point (ASTM D2295), °C | | **> 280** |
| Oil separation % loss (ASTM D1742) | | **2.5** |
| Copper Corrosion (ASTM D4048) | | **1B** |
| Water washout (ASTM D1264) @ 38°C | | **< 2% max.** |
| Four Ball Weld Load (IP 239) | | **315kg** |
| Four Ball Wear (IP 239), mm | | **0.70** |
| Operating Temperature Range, °C | | **-40°C to + 160** |

Typical values. They do not form a specification.

## PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0931

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063