FOOD GRADE

SARFOOD PAO GEAR OIL 220.

A fully synthetic food grade gear oil for gearboxes and reduction gears.

PRODUCT RANGE
Food Grade Gear Oils

218 cSt	280 °C	-35 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Gearboxes and reduction gears on food plant
- Conveyor and drive chain lubrication
- Mixers, augers and process drives
- Bakery, dairy and beverage line gearing

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	ingredients are FDA listed, grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives
Meets	the requirements of NSF and InS H1 Guidelines, the USDA 1998 H1 Guidelines

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear Adhesive Fluid**
Viscosity @ 40°C		**218**
Viscosity Index	ASTM D2270	**135**
Pour Point, °C		**-35**
Flash Point Open Cup, °C		**280**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SFG0220

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063