FOOD GRADE

SARFOOD PLUS 2 GREASE.

An aluminium complex food grade grease with white lubricating solids and PTFE, covering -50 °C to +170 °C, a span that takes it from a blast freezer to an oven area on the same site.

PRODUCT RANGE

Food Grade Greases

APPLICATION

- Heavily loaded bearings in food production
- Wet and saturated environments
- Dusty areas, flour, sugar and powder handling
- Sites spanning chilled and hot areas

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White tacky grease**
NLGI Classification		**No.2**
Thickener		**Aluminium Complex**
Drop Point (IP 132), °C		**> 230**
Base Oil		**Blend of synthetic base oils**
Solid Lubricant		**White lubricating solids and PTFE**
Copper Corrosion (IP 112)		**Negative**
Water washout (ASTM DS1264) @ 38°C		**< 1% max.**
Dynamic Corrosion Resistance (EMCOR) (IP 220)		**0:0**
Four Ball (IP 239) Weld Load		**400 kg**
Operating Temperature Range, °C		**-50°C to + 170**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients, nut oil or derivatives

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0896

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063