FOOD GRADE

# SARFOOD PLUS EP00 GREASE.

The semi-fluid version of Sarfood Plus, at NLGI 00 on the same aluminium complex thickener.

PRODUCT RANGE
**Food Grade Greases**

## APPLICATION

- Centralised lubrication systems on food plant
- Conveyor auto-lube installations
- Gearboxes designed for a semi-fluid grease
- Long lubrication lines in cold areas

**NOT RECOMMENDED**

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance | Visual | **Off White tacky grease** |
| NLGI Classification | | **00** |
| Thickener | | **Aluminium Complex** |
| Drop Point (IP 132), °C | | **> 230** |
| Base Oil | | **Blend of synthetic base oils** |
| Solid Lubricant | | **White lubricating solids** |
| Copper Corrosion (IP 112) | | **Negative** |
| Water washout (ASTM DS1264) @ 38°C | | **< 1% max.** |
| Dynamic Corrosion Resistance (EMCOR) (IP 220) | | **0:0** |
| Four Ball (IP 239) Weld Load | | **400 kg** |
| Operating Temperature Range, °C | | **-50°C to + 165** |

Typical values. They do not form a specification.

## PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

## BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 5 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **FDA** | listed ingredients |
| **NSF** | and InS H1 Guidelines |
| **USDA** | 1998 H1 Guidelines |
| **No** | genetically-modified ingredients |
| **Contains** | no nut oil or derivatives |

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0100

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063