FOOD GRADE

SARFOOD PREMIER EP00 GREASE.

A food grade calcium sulphonate grease on PAO base oil, the premium chemistry in the range.

PRODUCT RANGE
Food Grade Greases

APPLICATION

- Centralised systems needing premium performance
- Heavily loaded auto-lube installations
- Low to medium speed bearings in adverse conditions
- Wet, hot process areas

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth beige grease**
NLGI Classification		**No. 00**
Thickener		**Calcium Sulphonate**
Base Oil		**PAO**
Rust Test (ASTM D1743)		**Pass**
Copper Corrosion (ASTM D4048)		**1B**
Drop Point (IP 132), °C		**>270**
Timken OK Load (ASTM D2509)		**25 kg**
Shell Four Ball (IP239)		**Weld Load – 500 kg; Mean Hertz Load – 55 kg**
Operating Temperature Range, °C		**-40°C to +165**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
Water	Regulations Advisory Scheme (WRAS) approval
No	genetically-modified ingredients
Contains	no nut oil or derivatives

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0941

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063