FOOD GRADE

SARFOOD PTFE MULTI CHAIN OIL.

A food grade multi-purpose chain oil and penetrating lubricant carrying PTFE solid lubricant.

PRODUCT RANGE
Food Grade Chain Oils

APPLICATION

- Chains, bearings and slides in food areas
- Clean room and hygienic environments
- Penetrating and freeing seized components
- General maintenance lubrication in production

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	ingredients are FDA listed under 21 CFR 178.3570, grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives
Meets	the requirements of NSF and InS H1 Guidelines, the USDA 1998 H1 Guidelines

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale coloured liquid**
Base Oil Type		**Synthetic fluid**
Viscosity at 40°C, cSt		**150**
Operating Temperature Range, °C		**-50°C to +180**
Copper corrosion test (IP 112) (ASTM D130)		**1b**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IB0587

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063