FOOD GRADE

SARFOOD PTFE MULTILUBE 32.

The food grade equivalent of the can of maintenance oil that lives in every workshop, a light PTFE-fortified multi-purpose lubricant with penetrating and dewatering properties.

PRODUCT RANGE
Food Grade Multi-Purpose Oils

APPLICATION

- General maintenance lubrication after washdown
- Displacing water from hinges and slides
- Freeing and penetrating in production areas
- Light lubrication of conveyors and guides

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	ingredients are FDA listed under 21 CFR 178.3570

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale coloured liquid**
Base Oil Type		**Synthetic fluid**
Viscosity at 40°C, cSt		**26-32**
Solid lubricant		**PTFE**
Operating Temperature Range, °C		**-50°C to +180**
Copper corrosion test – (IP 112)(ASTM D130)		**1b**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MFL0030

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063