FOOD GRADE

SARFOOD STANDARD GREASE.

The workhorse food grade grease: a calcium 12-hydroxystearate soap on technical white oil, built for plant that gets washed down.

PRODUCT RANGE
Food Grade Greases

APPLICATION

- General bearing greasing on food plant
- Areas subject to frequent washdown
- Plain and anti-friction bearings
- Conveyors, mixers and packaging machinery

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

FOOD GRADE · CONTINUED

SARFOOD STANDARD GREASE.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients, nut oil or derivatives

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth Adhesive Grease**
Colour	ASTM D1500	**Off White**
NLGI Classification		**2**
Thickener		**Calcium 12 Hydroxy Stearate**
Base Oil		**Technical White Oil**
Water Washout (IP215) @ 38°C, %		**4**
Water Washout (IP215) @ 79°C, %		**8**
Dropping Point (IP132)		**140°C min**
Copper Corrosion (IP112)		**Pass**
Oil Separation (IP121) 7 days @ 40°C		**4% max**
Resistance To Corrosion EMCOR (IP220)		**0 : 0**
Four Ball Weld Load (IP239)		**315**
Scar Diameter For 1 Hr @ 40 kg, mm		**0.56**
Operating Temperature Range, °C		**-20°C to 110**
Worked Penetration (IP50)		**265 to 295**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0895

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063