FOOD GRADE

SARFOOD ULTRA CLEAR GEL.

A clear synthetic gel-like grease on a silica thickener with PTFE, non-melting, non-toxic and, importantly, visually clean.

PRODUCT RANGE
Food Grade Greases

APPLICATION

- Plastic components and O-rings
- Pharmaceutical and clean room equipment
- Display-facing and audited plant
- Plain and rolling element bearings needing a clean grease

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

FOOD GRADE · CONTINUED

SARFOOD ULTRA CLEAR GEL.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients, nut oil or derivatives

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White translucent grease**
NLGI Classification		**2**
Thickener		**Silica**
Drop Point (IP 132)		**Non melting**
Base Oil		**Blend of synthetic hydrocarbons**
Viscosity @ 40°C, cSt		**80**
Oil Separation	ASTM D6184	**None**
Solid Lubricant		**PTFE**
Water Washout (ASTM D1264) @ 38°C		**< 2% max.**
Dynamic Corrosion Resistance (EMCOR) (IP 220)		**0:0**
Shell Four Ball – Weld Load (IP239)		**210kg**
dN Factor		**500,000**
Operating Temperature Range, °C		**-40°C to +160**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0092

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063