FOOD GRADE

SARFOOD VHVI 32 AIRLINE OIL.

A food grade airline oil for the in-line lubricators feeding pneumatic equipment.

PRODUCT RANGE
Food Grade Airline Oils

APPLICATION

- Airline lubricators on packaging machinery
- Pneumatic cylinders and actuators
- Air tools used in production areas
- Compressed air systems needing a clean oil

NOT RECOMMENDED

- × Applications requiring an H2 or 3H registered product
- × Direct food contact, H1 covers incidental contact only

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

All	ingredients are FDA listed, grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives
Meets	the requirements of NSF and InS H1 Guidelines, the USDA 1998 H1 Guidelines

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear Fluid**
Base Fluid		**Synthetic Oil**
Viscosity @ 40°C, cSt		**28.8 – 35.2**
Specific Gravity @ 15°C g/mL		**0.865**
Operating Temperature Range, °C		**-15 to + 170**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L (Other pack sizes and bulk deliveries up to 25,000 litres available on request)

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SFA0100

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063