INDUSTRIAL OILS

SARGEAR 460 EP.

A sulphur-phosphorus EP industrial gear oil on solvent-refined mineral base stocks, built for enclosed gearboxes carrying real load.

PRODUCT RANGE
Industrial Gear Oils

APPLICATION

- Worm drives and heavily loaded reducers
- Hot-running gearboxes needing more film
- Applications specifying DIN 51517 Part 3 CLP

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51517 Part 3 (CLP)
ISO	12925-1 (CKC)
GB5903-2011 (CKC)	
JIS	K 2219:2006 (Class 2)
David	Brown S1.53.101(E)
AGMA	9005-E02
AIST	(US Steel) 229

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity @ 40°C		**460**
Density @ 15°C	ASTM D4052	**0.898**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IG0104

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063