INDUSTRIAL OILS

SARGEAR SYNTH PAG 320.

A 100% synthetic polyalkylene glycol EP gear oil, and a genuinely different animal from a mineral or PAO gear oil.

PRODUCT RANGE
Industrial Gear Oils

45 cSt	1.005	>225 °C	–30 °C
Viscosity @ 100°C	Density @ 20°C, kg/m³	Flash point	Pour point

APPLICATION

- Worm gearboxes, where the efficiency gain is largest
- Hot-running drives at the limit of a mineral oil
- Energy reduction projects on gear-driven plant
- Gearboxes specified for a PAG fill by the builder

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51517 Part 3 (CLP)
David	Brown Type G

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 20°C, kg/m³		**1.005**
Viscosity @ 100°C, mm²/s		**45**
Flash Point, °C		**>225**
Pour Point, °C		**–30**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PAG0320

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063