INDUSTRIAL OILS

SARGEAR SYNTH PAO 460.

A full synthetic Group IV polyalphaolefin gear and bearing oil for severe duty.

PRODUCT RANGE
Industrial Gear Oils

458 cSt	247 °C	-36 °C	Clear
Viscosity @ 40°C	Flash point	Pour point	Appearance

APPLICATION

- Wind turbine gearboxes and bearings
- Outdoor drives with a wide temperature swing
- Extended-drain industrial gearing
- Hot, heavily loaded reducers

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51517 Part 3
AGMA	9005-E02 (EP)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear**
Kinematic Viscosity @ 40°C		**458**
Viscosity Index (ASTM D2270)		**133**
Pour Point, °C		**-36**
Flash Point, (COC), °C		**247**
Foaming (ASTM D892) – After sequence 1		**Nil**
Foaming (ASTM D892) – After sequence 2		**Nil**
Copper Corrosion	ASTM D130	**1b**
Biodegradability % (ISO 9439)		**>60**
FZG Gear Test Stage		**13**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PAO0460

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063