GREASES

SARGREASE CBS 2.

A calcium sulphonate complex grease, the premium water-resistant chemistry, and one of the few greases where the thickener itself carries load.

PRODUCT RANGE

Calcium & Calcium Sulphonate Greases

220 cSt	>280 °C	No.2
Viscosity @ 40°C	Dropping point	NLGI grade

APPLICATION

- Steel mill and continuous casting bearings
- Marine deck machinery
- Extended lubrication intervals in wet, hot service
- Paper machine wet end bearings

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth, beige grease**
Thickener		**Calcium Sulphonate Complex**
NLGI Classification		**No.2**
Base Oil Viscosity@40°C (IP71), cSt		**220**
Water Washout (IP215, ASTM D1264), %		**<1**
Dropping Point (ASTM D1264), °C		**>280**
Operating temperature range, °C		**-30°C to +150°C, occasional peak to 220**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GRO911

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063