GREASES

SARGREASE PB 30M.

A hydrocarbon polymer liquid grease for very high temperature, slow speed bearings, the 180 °C to 300 °C range where every conventional grease has already failed.

PRODUCT RANGE

High Temperature Greases

APPLICATION

- Kiln and oven conveyor bearings
- Slow speed bearings above 180 °C
- Furnace trolley and roller bearings
- Where conventional greases carbonise and jam

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

PERFORMANCE PROFILE

Suitable where the following specifications are required:

NSF	H2

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Viscous liquid grease**
Colour	ASTM D1500	**Grey/black**
Base Oil Type		**Hydrocarbon polymer**
Copper (IP112)		**Negative**
Mild Steel (IP112)		**Negative**
Four Ball Weld Load (IP239)		**178kg**
Operating Temperature Range, °C		**180°C to 300**

Typical values. They do not form a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0130

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063