METALWORKING FLUIDS

SARGRIND CG PLUS.

A very high quality, fully synthetic soluble grinding fluid primarily designed to provide exceptional performance when grinding and regrinding using tungsten carbide tooling, engineered to prevent cobalt leaching, extend

PRODUCT RANGE
Soluble Grinding Fluids

APPLICATION

- Carbide grinding
- Ceramics
- Cermets
- Chill cast alloys
- Tool steels
- Non-ferrous metals
- Copper-based and aerospace alloys

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (Concentrate)		**Amber liquid**
Appearance (Solution)		**Clear fluorescent yellow**
pH (5% emulsion)		**9.2**
IP 287 Breakpoint, %		**2.0**
Mineral Oil Content		**Nil**
Refractometer Conversion Factor		**1.72**
Make Up Water Hardness, ppm		**50 – 600**
Concentration, %		**3% – 5**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IF0022

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063