INDUSTRIAL OILS

SARLUBE OIL 68.

A straight, solvent-refined mineral machine oil with no EP or anti-wear package, and that simplicity is the point.

PRODUCT RANGE
General Purpose Oils

0.881	210 °C	Liquid	Amber
Density @15.6	Flash point	pH	Colour

APPLICATION

- Total-loss oilers and drip feed lubrication
- Plain bearings and pillow blocks
- Textile machinery general lubrication
- Chains, slides and open lubrication points

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL1

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Physical form		**Liquid**
Colour	ASTM D1500	**Amber**
Odour		**Oily**
Boiling Point (Typical), °C		**225**
Viscosity @ 40°C, cSt		**61.2 – 74.8**
Flashpoint °C (C.C)		**210**
Density @15.6, °C		**0.881**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO0032

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063