INDUSTRIAL OILS

SARMAX FILTRO HYDRAULIC OILS – ISO 32.

The standard SARMAX hydraulic oil taken a stage further: after blending, every batch is filtered to a far tighter cleanliness code than a normal industrial fill.

PRODUCT RANGE
Hydraulic Oils

32 cSt	4.9 cSt	0.876	205 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Commissioning fills on new machine tools
- Servo and proportional valve hydraulics
- Systems with a written ISO 4406 cleanliness target
- Top-ups that must not raise the particle count

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51524 Part 2 (HLP)
Denison	HF-2, HF-1, HF-0, Filterability TP 02100
Sperry	Vickers 1-286-SC
Cincinnati	Milacron P-68, P-70
AFNOR	NF E 48-603 (HM)
FZG	Damaging Stage 12
US	Steel 126 / 127 For R & O Hydraulic Fluids

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity @ 40°C		**32**
ISO Viscosity @ 100°C		**4.9**
Density @ 15°C	ASTM D4052	**0.876**
Pour Point, °C		**-24**
Flash Point (COC), °C		**205**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HY0014

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063