INDUSTRIAL OILS

SARMAX HFC 46.

A fire-resistant HFC hydraulic fluid: polyalkylene glycols dissolved in a stable water solution, so roughly 44% of what is in the tank is water.

PRODUCT RANGE
Hydraulic Oils

APPLICATION

- Die casting and forging press hydraulics
- Furnace door and charging gear
- Any hydraulic circuit with a credible ignition source nearby
- Applications where an HFC fluid is written into the insurer's requirements

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pink coloured liquid**
ISO Grade		**46**
Viscosity @ 40°C		**43.0 – 49.0**
Viscosity Index	ASTM D2270	**> 200**
Water Content, %	ASTM D6304	**44**
IP 135 Rust Test (Part 1)		**No rust**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HG0046

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063