INDUSTRIAL OILS

SARMAX HFDU HYDRAULIC 68.

A fire-resistant HFDU fluid based on synthetic esters, which does something a water-glycol cannot: it is fire resistant and fully biodegradable and behaves much more like a conventional oil in the pump.

PRODUCT RANGE
Hydraulic Oils

65 cSt	0.928	290 °C	-32 °C
Viscosity @ 40°C	Density @ 20°C g/cm³	Flash point	Pour point

APPLICATION

- Fire risk areas that also need environmental cover
- Dockside cranes and lock gear
- Hydro and water-industry hydraulics
- Tunnelling and underground plant

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 4 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

INDUSTRIAL OILS · CONTINUED

SARMAX HFDU HYDRAULIC 68.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FM	approved formulation
ISO	15380:2016 (international standard for environmentally acceptable hydraulic fluids), 6743-4:2015 (rapidly-biodegradable hydraulic fluids, HEES class)
VDMA	24568 (environmentally-friendly hydraulic fluids based on synthetic esters, HEES class)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Yellow – Brownish**
Density @ 20°C, g/cm³		**0.928**
Viscosity @ 20°C, mm²/s		**158**
Viscosity @ 40°C, mm²/s		**65**
Viscosity @ 50°C, mm²/s		**45**
Viscosity Index	ASTM D2270	**185**
Flash Point, °C		**290**
Fire Point, °C		**375**
Pour Point, °C		**-32**
Auto Ignition Temp, °C		**490**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HF0068

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063