INDUSTRIAL OILS

SARMAX HYDRAULIC BIO 15.

A readily biodegradable hydraulic oil built on vegetable base oils with a completely biodegradable, ashless additive system and no zinc at all.

PRODUCT RANGE
Hydraulic Oils

APPLICATION

- Forestry harvesters, forwarders and cranes
- Plant working on or beside water
- Groundcare and amenity machinery in public spaces
- Sites operating under an environmental permit

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ISO	15380:2016, 6743-4:2015
VDMA	24568
Cincinnati	Milacron P-38 (Bio 32), Milacron P-55 (Bio 46), Milacron P-54 (Bio 68)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber oil**
Specific Gravity @ 15.6°C		**0.907 – 0.940**
Phosphorus, % wt		**0.005**
Nitrogen, % wt		**0.027**
Zinc, % wt		**Nil**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HA0505

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063