INDUSTRIAL OILS

SARMAX HYDRAULIC OILS – ISO 460.

A zinc-based anti-wear hydraulic oil built on solvent-refined Group I mineral base stocks and a balanced HM additive package.

PRODUCT RANGE
Hydraulic Oils

460 cSt	30.0 cSt	0.896	255 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- The heaviest hydraulic and circulation duties
- Slow, high-load industrial rams
- Hot, heavily loaded plant

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity @ 40°C		**460**
ISO Viscosity @ 100°C		**30.0**
Density @ 15°C	ASTM D4052	**0.896**
Pour Point, °C		**-7**
Flash Point (COC), °C		**255**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 11 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51524 Part 2 (HM, HLP)
ISO	11158 (HM)
ASTM	D6158 (HM)
SAE	MS1004 (HM)
Bosch Rexroth	RDE 90235
Eaton	E-FDGN-TB002-E
GB	11118.1-2011 (L-HL, L-HM)
JCMAS	P041 HK Hydraulic specification
GM	LS-2
SEB	181222
AIST-US Steel	126/127 – R & O Hydraulic Fluids

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HY0014

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063